

# Technical Data Sheet



## Acryline Cold Applied Fast Dry Waterborne



### Characteristics:

- ❖ Low VOC
- ❖ Environmentally friendly
- ❖ Excellent color retention
- ❖ Spreading rate of 300 linear feet per gallon of 4-inch line
- ❖ Non-flammable
- ❖ Non-bleeding
- ❖ Excellent glass bead retention and night visibility
- ❖ Easy clean-up with soap and water
- ❖ Recommended for sealcoated surfaces

### Cautions:

- ❖ Smooth surfaces should be roughened for better bonding
- ❖ Keep from freezing
- ❖ Addition of water or other soluble solvents will adversely affect dry time
- ❖ All equipment should be cleaned before paint dries

### Specifications

|   |  |
|---|--|
| <b>Viscosity:</b> 85 – 95 Krebs Units   | <b>Total Solids:</b> 70 % Minimum                            |
| <b>Weight per Gallon:</b> 13.50 Minimum   | <b>Dry to NPU:</b> 5 to 15 Minutes track free at 15 mils wet |
| <b>Shelf Life:</b> 1 Year Minimum Properly Stored   | <b>Vehicle Type:</b> 100% Acrylic Binder                     |
| <b>Water Resistance:</b> 3 hours minimum drying at temperatures above 50°F and humidity below 80% before exposure to moisture |  |

# CROWN USA INCORPORATED

Crown USA, Inc.  
20180 Safety Lane  
Post Office Box 399  
Foley, AL 36536

P: (706)553-9500  
F: (706)553-9501  
[www.crownusa.com](http://www.crownusa.com)  
[info@crownusa.com](mailto:info@crownusa.com)